



ALCOLIN READY-TO-USE LATEX-BOND CEMENT ADDITIVE

Characteristics

ALCOLIN READY-TO-USE LATEX-BOND CEMENT ADDITIVE is a ready to use cement additive that has been specially formulated to replace the water addition component of cement based products e.g. cement plaster, concrete, screeds, cement based tile adhesives and grouts.

Features

- Ready to use – no dilution required
- Improves performance of cement-based products
- Mixes readily into cement-based products
- Will not influence key properties such as setting times of cement based products

Applications

- ALCOLIN LATEX-BOND is used where extra performance may be required such as improved adhesion, enhanced water resistance and increased flexural strength.
- ALCOLIN LATEX-BOND will not influence the original products unique characteristics such as setting time though grouts may dry a shade darker than those with a straight water addition

Restrictions on use

Cannot be mixed with cretestone or gypsum-based products

Safety instructions

Do not ingest. Keep away from children and pets. Do not empty into drains. Wear rubber gloves. Avoid contact with eyes. Allow any unused product to dry before disposing of the container. In the event of skin contamination, rinse thoroughly with cold water. Seek medical assistance if irritation or discomfort persists. Refer to our Material safety data sheets for further toxicological information and comprehensive handling instructions

Storage stability

ALCOLIN LATEX-BOND must be kept in an airtight container and stored at a moderate temperature and out of direct sunlight. The product has a shelf life of approximately 12 months if stored as described above in its original sealed moisture tight container



Directions for use

➤ **Mixing**

ALCOLIN LATEX-BOND is a ready to use product and must not be adulterated by addition of water or any other substance other than that which has been specified for use. Shake before use

➤ **Application**

Refer to the individual details and mixing instructions for each ALCOLIN cement based product that is to be used, where the ALCOLIN LATEX-BOND is to be substituted for the water addition component

➤ **Curing**

ALCOLIN LATEX-BOND will not affect the normal setting times of cement-based products; these may dry a shade darker

➤ **Coverage**

Refer to the cement-based product being used for the application to determine the coverage

Product data

Colour	White
Consistency	Low viscosity liquid
Density (g/cm ³)	1.0

Product packaging

Size: 1L and 5L plastic containers



The above information is only offered, as a guide to the use of this product. Furthermore, users should satisfy themselves that it is suitable for their needs. Since we have no control over the conditions under which it is used, we cannot accept responsibility for problems caused by the use and/or application of this product.

Head Office: +27-21-555-7400
Toll-Free No: 0800-222-400
Beverly Close, Montague Gardens, 7441
PO Box 37008, Chempet, 7442
www.alcolin.com

