



ALCOLIN EPOXY FLOOR PAINT

SAFETY DATA SHEET

PART A

1. IDENTIFICATION

1.1. Product identifier

Product name Alcolin Epoxy Floor Paint (Base)
Chemical family Epoxy Resin

1.2. Intended use of the product

2-part filled water based Epoxy Floor Paint

1.3. Name, address, and telephone of the responsible party

Company: Permo seal (PTY) Ltd
Address: 1 Beverley Close, Montague Gardens, 7441, Cape Town, South Africa
Phone: +27-21-555-7400
Toll-free No. 0800-222-400
Website: www.alcolin.com

1.4. Emergency phone number

+27-21-555-7400

2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

GHS Classification This product is classified as a hazardous mixture

2.2. Label elements

GHS Labelling

- This product is classified and labelled according to the CLP regulation.
- Hazard pictograms**



GHS07



GHS09

2.3. Signal word

Warning

2.4. Hazard determining components of labelling:

Reaction product: Bisphenol-A epichlorhydrin epoxy resin

2.5. Hazard statements:

H315 Causes skin irritation.
H317 May cause an allergic skin reaction
H319 Causes serious eye irritation.
H411 Harmful to aquatic life with long lasting effects.

2.6. Precautionary statements:

P261	Avoid breathing vapours.
P273	Avoid release to the environment.
P280	Wear protective gloves / eye protection.
P302+P352	If on skin: Wash with plenty of soap and water.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Seek medical attention.
P501	Dispose of contents/containers in accordance with national regulations.

2.7. Additional information

Contains epoxy constituents. May produce an allergic reaction.

2.8. Other hazards

No additional information available.

2.9. Unknown acute toxicity

No data available

3. COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Mixture. This product is hazardous.

3.2 Hazardous Components

Hazardous Component	CAS No.	Contents (%)	Classification of Substances
Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)	25068-38-6	25 - 32	Eye irritation: Cat 2 Skin irritation.: Cat 2 Skin sensitization.: Cat 1 Aquatic chronic: Cat 2
Oxirane, 2-(chloromethyl)-, polymer with alpha-hydro-omega-hydroxypoly[oxy(methyl-1,2-ethanediyl)]	9072-62-2	4 - 7	Skin sensitization: Cat 1
4-Nonylphenol, branched, ethoxylated	127087-87-0	<1.5	Aquatic chronic: Cat 3

4. FIRST-AID MEASURES

4.1. Description of first aid measures

General	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice.
Inhalation	Remove victim to fresh air. Seek medical attention.
Skin contact	Wash skin with soap and water and rinse thoroughly. Seek medical attention if irritation persists.
Eye contact	Rinse cautiously with water for 15 minutes. Remove any contact lenses if present and easy to do. Continue rinsing. Obtain medical attention.
Ingestion	Rinse mouth. Do not induce vomiting. Get the affected person to drink a lot of water in small gulps. Obtain medical attention.

4.2. Most important symptoms and effects both acute and delayed

General	May cause irritation in the uncured state.
Inhalation	Irritates respiratory passages very slightly.
Skin contact	May cause sensitization by skin contact. Contains epoxy constituents, may produce an allergic reaction.
Eye contact	Direct contact may cause moderate irritation.
Ingestion	May be harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians	Treat symptomatically
--------------------	-----------------------

5. FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media	Water spray, dry chemical powder, alcohol-resistant foam, carbon dioxide
Unsuitable ext. media	Do not use a high pressure water jet

5.2. Special hazards arising from the substance or mixture

Fire hazard	Not flammable
Explosion hazard	Product is not explosive

5.3. Advice for firefighters

Firefighting instructions	Exercise caution when fighting any chemical fire.
Protection during firefighting	Firefighters should wear full protective gear. Do not enter fire area without proper protective equipment, including respiratory protection.
Hazardous combustion products	Under certain conditions of combustion, traces of toxic substances cannot be excluded.

6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

General measures	Contaminated surfaces will become very slippery.
------------------	--

6.2. For non-emergency personnel

Protective equipment	Use appropriate personal protection equipment (PPE)
Emergency procedures	Evacuate unnecessary personnel.

6.3. For emergency personnel

Protective equipment	Use appropriate personal protection equipment (PPE)
Emergency procedures	Secure the area and evacuate unnecessary personnel.

6.4. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.5. Methods and materials for containment and cleaning up

For containment	Absorb and or contain spill with inert material.
Methods for cleaning up	If recovery is not feasible, absorb with inert material. Place in a container suitable for disposal. Dispose of in accordance with current local legislation.

6.6. Reference to other sections

Refer to Section 8, Exposure controls and personal protection

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Handling temperature	Normal ambient temperature
Hygiene measures	Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating or drinking.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	Store in a dry, cool and well-ventilated place. Keep container closed when not in use.
Incompatible materials	Organic solvents, strong acids, strong alkalis and salts. Reacts with amines.
Maximum storage period	24 months, but may vary depending on storage conditions.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

8.1. Control parameters

There are no established exposure limits for this product.

8.2. Exposure controls

Engineering controls	Provide good ventilation when handling large quantities. No special measures are required if stored and handled as above.
Hand protection	Wear chemical resistant, impermeable gloves
Eye protection	Safety glasses
Skin and body protection	Use a protective suit
Respiratory protection	Not required under normal conditions of use in a well-ventilated space
Other information	When using, do not eat or drink

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Off-white, dark grey, beige viscous liquid
Odour	Characteristic
Density (g/cm ³)	Approximately 1.56
Flash point (°C)	> 100
Solubility water	Insoluble

10. STABILITY AND REACTIVITY

Reactivity	None expected under normal conditions
Chemical stability	Stable under normal conditions
Possibility of hazardous reactions	None expected under normal conditions.
Conditions to avoid	Direct sunlight. Extremely high or low temperatures
Incompatible materials	Organic solvents, strong acids, strong alkalis and salts. Reacts with amines.
Hazardous decomposition products	Thermal decomposition releases carbon dioxide and carbon monoxide

11. TOXICOLOGICAL INFORMATION

This product has not undergone any toxicological testing. Acute and chronic health effects are not expected as long as good industrial hygiene and safety precautions are followed.

11.1. Information on toxicological effects

- Acute Toxicity:**

Ingredient	Result	Species	Dose
Bisphenol-A-(epichlorhydrin);	LD ₅₀ Dermal	Rabbit	23000 mg/kg
epoxy resin	LD ₅₀ Oral	Rat	>15000 mg/kg

12. ECOLOGICAL INFORMATION

This product has not been tested for environmental effects. It is however toxic to fish and other aquatic organisms and poses a danger to drinking water if even small quantities leak into the ground.

- Toxicity:**

Ingredient	Result	Species	Exposure
Bisphenol-A-(epichlorhydrin); epoxy resin	EC ₅₀ 11mg/l	Aquatic plants	72 hours
	EC ₅₀ 1.8mg/l	Daphnia	48 hours
	LC ₅₀ 2mg/l	Fish	96 hours
	Chronic NOEC 0.3mg/l	Daphnia	-

13. DISPOSABLE CONSIDERATIONS

Sewage disposal recommendations	Do not dispose waste into sewer.
Waste disposal recommendations	Whatever cannot be saved for recovery or recycling should be disposed of in accordance with current local legislation.

14. TRANSPORT INFORMATION

14.1. UN Number


ADR, ADN, IMDG, IATA UN 3082

14.2. UN Proper Shipping Name

ADR, ADN, IMDG, IATA Environmentally hazardous substance, liquid, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin)

14.3. Transport hazard class

ADR, ADN, IMDG, IATA LABEL



CLASS 9 Miscellaneous dangerous substances and articles

14.4. Packing group

ADR, ADN, IMDG, IATA III

14.5. Environmental hazards

Marine pollutant (IMDG), Special marking (ADR/AND), Special marking (IATA)



14.6. Special precautions for user Warning: Miscellaneous dangerous substances and articles

15. REGULATORY INFORMATION

15.1. Labelling Classified as a hazardous product

15.2. National legislation None

16. OTHER INFORMATION

16.1. Information sources

This SDS is prepared based on the information received from the suppliers

16.2. Full text of H-phrases referred to under Section 3

H315 Causes skin irritation.

H317 May cause an allergic skin reaction

H319 Causes serious eye irritation.

H411 Harmful to aquatic life with long lasting effects.

16.3. Additional information

This document has been prepared in accordance with the SDS requirements of SANS 11014:2010

For intended use and applications see the Technical Data Sheet for the product. The information provided in this Safety Data Sheet is based on the present state of our knowledge. This data is intended to enable safety assessments to be made and should not be construed as guaranteeing specific properties. Recipients of our product must take responsibility for observing existing laws and regulations.

Revision date 01/ April 2020



ALCOLIN EPOXY FLOOR PAINT

SAFETY DATA SHEET

PART B

1. IDENTIFICATION

1.1. Product identifier

Product name Alcolin Epoxy Floor Paint (Activator)
Chemical family Polyamide

1.2. Intended use of the product

The activator (also known as the hardener or curing agent) of a 2-part epoxy system

1.3. Name, address, and telephone of the responsible party

Company: Permo seal (PTY) Ltd
Address: 1 Beverley Close, Montague Gardens, 7441, Cape Town, South Africa
Phone: +27-21-555-7400
Toll-free No. 0800-222-400
Website: www.alcolin.com

1.4. Emergency phone number

+27-21-555-7400

2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

GHS Classification This product is classified as a hazardous mixture

2.2. Label elements

GHS Labelling

- This product is classified and labelled according to the CLP regulation.

- Hazard pictograms**



GHS07



GHS05

2.3. Signal word: Warning

2.4. Hazard determining components of labelling:

Polyamine/polyamide mixture

2.5. Hazard statements

H315 Causes skin irritation
H318 Causes serious eye irritation
H317 May cause an allergic skin reaction

2.6. Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves / eye protection.
P280e Wear protective gloves
P264 Wash hands thoroughly after handling

P272 Contaminated clothing should not be allowed out of the work place
P302+P352 If on skin: Wash with plenty of soap and water.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 If skin irritation or rash occurs: Seek medical attention.
P501 Dispose of contents/containers in accordance with national regulations.

2.7. Other Hazards

Contains Linseed oil which may cause an allergic skin reaction on prolonged contact. Contains epoxy constituents. May produce an allergic reaction. Repeated exposure may cause skin sensitization.

2.8. Other Hazards

No additional information available.

2.9. Unknown acute toxicity

No data available

3. COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Mixture. This product is hazardous

3.2 Hazardous Components

HAZARDOUS COMPONENT	CAS NUMBER	PERCENTAGE	Classification of substance
Linseed oil, polymer w/bis-A diglycidyl ether, diethylenetriamine, formaldehyde, glycidyl Ph ether, pentaethylenehexamine	68915-81-1	<50%	Eye damage: Cat 1 Skin irrit.: Cat 2
Pentaethylenehexamine	4067-16-7	<1%	Skin corr.: Cat 1B Skin sens.: Cat 1 Aquatic acute: Cat 1 Aquatic chron.: Cat 1
Acetic acid	64-19-7	<1%	Skin corr.: Cat 1A Flam. Liq.: Cat 3
Tetraethylenepentamine	112-57-2	<1%	Skin corr.: Cat 1B Aquatic chron.: Cat 2 Acute tox.: Cat 4 Skin sens.: Cat 1
Diethylenetriamine	111-40-0	<1%	Acute tox.: Cat 4 Skin corr.: Cat 1B Skin sens.: Cat 1

4. FIRST-AID MEASURES

4.1. Description of first aid measures

General Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice.
Inhalation Take victim into fresh air. In case of unconsciousness, place patient in a recovery position for transportation. Seek medical advice.
Skin contact Wash skin with soap and water and rinse thoroughly. Seek medical attention if irritation persists.
Eye contact Rinse cautiously with water for 15 minutes. Remove any contact lenses if present and easy to do. Continue rinsing. Obtain medical attention.
Ingestion Rinse mouth thoroughly with water. Do not induce vomiting. Obtain medical attention.

4.2. Most important symptoms and effects both acute and delayed

General May cause irritation in the uncured state.
Inhalation May cause damage to organs through prolonged or repeated exposure.
Skin contact May cause sensitization by skin contact. Contains epoxy constituents, may produce an allergic reaction.
Eye contact May cause eye irritation.
Ingestion May be harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically



5. FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media	Dry chemical powder, alcohol-resistant foam, carbon dioxide, sand
Unsuitable ext. media	Not applicable

5.2. Special hazards arising from the substance or mixture

Fire hazard	Not flammable
Explosion hazard	Product is not explosive

5.3. Advice for firefighters

Firefighting instructions	Exercise caution when fighting any chemical fire.
Protection during firefighting	Firefighters should wear full protective gear. Do not enter fire area without proper protective equipment, including respiratory protection.
Hazardous combustion products	Under certain conditions of combustion, traces of toxic substances cannot be excluded.

6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

General measures	Contaminated surfaces will become very slippery.
------------------	--

6.2. For non-emergency personnel

Protective equipment	Use appropriate personal protection equipment (PPE)
Emergency procedures	Evacuate unnecessary personnel.

6.3. For emergency personnel

Protective equipment	Use appropriate personal protection equipment (PPE)
Emergency procedures	Secure the area and evacuate unnecessary personnel.

6.4. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.5. Methods and materials for containment and cleaning up

For containment	Absorb and or contain spill with inert material.
Methods for cleaning up	If recovery is not feasible, absorb with inert material. Place in a container suitable for disposal. Dispose of in accordance with current local legislation.

6.6. Reference to other sections

Refer to Section 8, Exposure controls and personal protection

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Handling temperature	Normal ambient temperature
Hygiene measures	Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating or drinking.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	Store in a dry, cool and well-ventilated place. Keep container closed when not in use.
Incompatible materials	Oxidizing agents, mineral acids and bases
Maximum storage period	24 months, but may vary depending on storage conditions.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

8.1. Control parameters

Exposure limits:

Name	TWA	STEL
Acetic acid	10 ppm; 25 mg/m ³	15 ppm; 37 mg/m ³
Tetraethylenepentamine	1 ppm; 5 mg/m ³	-
Diethylenetriamine	1 ppm; 4 mg/m ³	-

8.2. Exposure controls

Engineering controls	Provide good ventilation when handling large quantities. No special measures are required if stored and handled as above
Personal protective equipment	Use appropriate personal protection equipment (PPE)
Hand protection	Wear chemical resistant, impervious gloves
Eye protection	Safety glasses
Skin and body protection	Use a protective suit
Respiratory protection	Not required under normal conditions of use in a well-ventilated space
Other information	When using, do not eat or drink

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Yellow liquid
Odour	Ammoniacal
pH	Approximately 9.4
Relative density (g/cm ³)	1.05
Boiling Point/Range	100
Flash point (°C)	> 100
Auto-ignition temperature (°C)	>150
Flammability	Not applicable
Solubility water	No data available

10. STABILITY AND REACTIVITY

Reactivity	None expected under normal conditions
Chemical stability	Stable under normal conditions
Possibility of hazardous reactions	None expected under normal conditions
Conditions to avoid	Direct sunlight. Extremely high or low temperatures
Incompatible materials	Oxidizing agents, mineral acids and bases
Hazardous decomposition products	Thermal decomposition may release carbon dioxide and carbon monoxide

11. TOXICOLOGICAL INFORMATION

This product has not undergone any toxicological testing. Acute and chronic health effects are not expected as long as good industrial hygiene and safety precautions are followed.

11.1. Additional toxicological information:

This product contains no listed carcinogens according to IAC, ACGIH and/or OSHA in concentrations of 0.1% or greater. Repeated or prolonged contact causes sensitization, asthma, eczemas. Adverse eye effects (such as conjunctivitis or corneal damage). Eye disease. Skin disorders and allergies. Adverse skin effects (such as rash, irritation or corrosion). Adverse respiratory effects (such as cough, tightness of chest or shortness of breath) Asthma.

12. ECOLOGICAL INFORMATION

This product has not been tested for environmental effects. However, the ingredients indicate that it is dangerous to the environment. May cause long term adverse effects in the aquatic environment. Contamination of the terrestrial and aquatic environments should be avoided. Please refer to section 6 for information regarding accidental release.

13. DISPOSABLE CONSIDERATIONS

Sewage disposal recommendations	Do not dispose waste into sewer.
Waste disposal recommendations	Whatever cannot be saved for recovery or recycling should be disposed of in accordance with current local legislation.

14. TRANSPORT INFORMATION

Road / rail transport	ADR / RID	Not regulated
Marine Transport	IMDG	Not regulated
Inland waterways	ADNR	Not regulated
Air transport	IATA	Not regulated

15. REGULATORY INFORMATION

15.1. Labelling	Classified as a hazardous product
15.2. National legislation	None

16. OTHER INFORMATION

16.1. Information sources

This SDS is prepared based on the information received from the suppliers

16.2. Full text of H-phrases referred to under Section 3

H315	Causes skin irritation.
H318	Causes serious eye irritation.
H317	May cause an allergic skin reaction

16.3. Additional information

This document has been prepared in accordance with the SDS requirements of SANS 11014:2010

For intended use and applications see the Technical Data Sheet for the product. The information provided in this Safety Data Sheet is based on the present state of our knowledge. This data is intended to enable safety assessments to be made and should not be construed as guaranteeing specific properties. Recipients of our product must take responsibility for observing existing laws and regulations.

Revision date 01/April 2020