



# ALCOLIN PAINT STRIPPER

## Description

ALCOLIN HEAVY DUTY PAINT STRIPPER is a heavy-duty paint and coating remover, which is non-flammable, super strong and quick acting. It has a non-alkali formula, which is solvent-based and will not damage bared surfaces

## Features & Benefits

- High viscosity – can apply on vertical surfaces
- Methylene chloride based – fast acting
- Does not contain alkali or acid - will not damage glass, wood, metal and plaster
- Non flammable – no fire risk
- Contains surfactant – improves penetration of stripper
- Contains wax – keeps the stripper active for longer

## Applications

- Removes coatings from wood, plaster, metal and glass
- Removes enamel paints
- Removes varnishes
- Softens acrylic paints and old glue
- Removes bitumen

## Limitations

- Should not be used on vinyl, plastic, fiberglass, rubber or plasterboard
- May not remove some two part acid catalyzed varnishes
- Will not remove deep stains
- May remove colour from textiles and leather

## Safety instructions

**Open ALCOLIN PAINT STRIPPER container with caution and away from face as contents may be under pressure**

When working with product, it is advisable to wear gloves and safety glasses in order to avoid direct contact with the skin or eyes. If product comes in contact with skin or eyes, flush thoroughly and immediately with water. If irritation continues, seek medical attention

Always work in a well-ventilated area. Do not breathe in vapours. For unventilated areas, a NIOSH approved respirator will be necessary

Keep ALCOLIN PAINT STRIPPER out of reach of children!

Refer to our Material Safety Data Sheets for further toxicological information and comprehensive handling instructions



## Surface preparation

- Ensure good ventilation by opening all windows before use
- Remove all loose material from surface
- Sanding the surface will speed up the stripping process

## Directions for use

- Do not dilute ALCOLIN PAINT STRIPPER
- Apply ALCOLIN PAINT STRIPPER to small areas at a time with a brush
- Spread a heavy layer evenly over the surface. Do not brush it out thinly like paint
- Leave for approximately 15 minutes until paint or coating has softened
- Remove paint with metal scraper. Steel wool can be used in difficult areas
- More than one application may be needed to completely remove the coating; therefore repeat the application if necessary
- Wipe the scraped surface with water to remove any excess ALCOLIN PAINT STRIPPER and allow the surface to dry
- Dispose of removed paint carefully
- Keep lid closed between applications

## Notes

Some coatings are difficult to remove, such as two part varnishes, acrylic paints and old glue. To improve efficiency of ALCOLIN PAINT STRIPPER, cover the applied product with plastic sheeting (tape in place if necessary) and leave for 1 hour. This prevents the drying out of the stripper and the active solvent component has more time to soften the coating

## Storage stability

ALCOLIN PAINT STRIPPER has a shelf life of at least 12 months if stored in a cool (below 25°C), dry place in its original moisture-tight container

If the material is kept beyond the recommended shelf life, it is not necessarily unusable, but a check should be performed to observe whether the product is still useable

To maximize the shelf life of the opened container, it would be advisable to create an airtight environment by screwing on the lid tightly after use and storing in a cool environment

## Product packaging

- 500ml tin
- 1 litre tin
- 5 litre tin

## Product data

### i. Physical data

Appearance	Translucent paste
Solvent	Methylene chloride
Density	Approximately 1.10
Solids	Approximately 3%
Viscosity	Approximately 10,000 cps
Softening time	10 to 20 minutes on enamels
Coverage	Approximately 1m <sup>2</sup> per liter

# TECHNICAL DATA SHEET

*The above information is only offered, as a guide to the use of this product. Furthermore, users should satisfy themselves that it is suitable for their needs. Since we have no control over the conditions under which it is used, we cannot accept responsibility for problems caused by the use and/or application of this product.*

Head Office: +27(0)21 555 7400  
Toll free no: 0800 222 400  
1 Beverley Close, Montague Gardens  
PO Box 37008, Chempet, 7442  
[www.alcolin.com](http://www.alcolin.com)

