



ALCOLIN SOLDERLENE

SAFETY DATA SHEET

1. IDENTIFICATION

1.1. Product identifier

Product name Alcolin Solderlene
Chemical family Nitrocellulose/solvent mixture

1.2. Intended use of the product

A non-conductive liquid cold solder

1.3. Name, address, and telephone of the responsible party

Company: Permo seal (Pty) Ltd
Address: 1 Beverley Close, Montague Gardens, 7441, Cape Town, South Africa
Phone: +27-21-555-7400
Toll-free No. 0800-222-400
Website: www.alcolin.com

1.4. Emergency phone number

+27-21-555-7400

2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

GHS Classification This product is hazardous

2.2. Label elements

GHS Labelling

- This product is classified and labelled according to the CLP regulation.
- Hazard pictogram:



GHS02



GHS07

2.3. Signal word Danger

2.4. Hazard determining components of labelling:

Methyl Ethyl Ketone, n-Butyl Acetate

2.5. Hazard statements:

H225 Highly flammable liquid and vapour
H228 Flammable solid
H315 Causes skin irritation
H319 Causes serious eye irritation
H335 May cause respiratory irritation
H336 May cause drowsiness or dizziness
H360 May damage fertility or the unborn child
H411 Toxic to aquatic life with long lasting effects

2.6. Precautionary statements:

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243	Take precautionary measures against static discharge
P280	Wear protective gloves / eye protection.
P273	Avoid release to the environment.
P201	Obtain special instructions before use.
P308+P313	If exposed or concerned: get medical advice/attention.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P403+233	Store in a well ventilated place. Keep container tightly closed.

2.7. Other Hazards

No additional information available

2.8. Unknown acute toxicity

No data available

3. COMPOSITION / INFORMATION ON INGREDIENTS

Mixture. This product is hazardous.

Ingredient	CAS No.	Contents (%)	Classification of Substance
Methyl Ethyl Ketone	78-93-3	50 - 60	Flam liq.: Cat 2 Eye Irrit.: Cat 2 STOT SE: Cat 3
n-Butyl Acetate	123-86-4	5 - 15	Flam liq.: Cat 3 STOT SE: Cat 3
Nitrocellulose chips damped with Di-Butyl Phthalate	9004-70-0 84-74-2	30 – 40	Flam liq.: Reprod.: Cat 1B Aquatic cute: Cat 1
Alum Paste		10 - 15	Flam solid: Cat 1 STOT SE: Cat 3 Asp tox.: Cat 1

4. FIRST-AID MEASURES

4.1. Description of first aid measures

General	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice.
Inhalation	Move to fresh air and seek medical attention if nausea and dizziness persists. Aspiration into lungs may lead to pneumonitis.
Skin contact	Wash skin with mild soap and water. Seek medical attention if irritation persists.
Eye contact	Rinse cautiously with water for 15 minutes. Remove any contact lenses if present and easy to do. Continue rinsing. Seek medical attention if any discomfort continues.
Ingestion	Rinse mouth. Do not induce vomiting. Get the affected person to drink a lot of water in small gulps. Obtain medical attention.

4.2. Most important symptoms and effects both acute and delayed

General	May cause irritation.
Inhalation	May cause irritation to the respiratory system. Prolonged inhalation may cause headaches, drowsiness and fatigue. High concentrations of vapours are anesthetic in nature causing central nervous system effects such as dizziness and confusion.
Skin contact	May cause skin irritation. Repeated exposure may lead to dermatitis.
Eye contact	May cause eye irritation.
Ingestion	May be harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians	Treat symptomatically
--------------------	-----------------------

5. FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media	Dry chemical powder, foam, carbon dioxide
Unsuitable ext. media	Do not use a water spray

5.2. Special hazards arising from the substance or mixture

Fire hazard	Highly flammable
Explosion hazard	Product is not explosive

5.3. Advice for firefighters

Firefighting instructions	Exercise caution when fighting any chemical fire.
Protection during firefighting	Firefighters should wear full protective gear. Do not enter fire area without proper protective equipment, including respiratory protection.
Hazardous combustion products	Under certain conditions of combustion, traces of toxic substances cannot be excluded.

6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

General measures	Do not get in eyes or skin, or on clothing.
------------------	---

6.2. For non-emergency personnel

Protective equipment	Use appropriate personal protection equipment (PPE)
Emergency procedures	Evacuate unnecessary personnel.

6.3. For emergency personnel

Protective equipment	Use appropriate personal protection equipment (PPE)
Emergency procedures	Secure the area and evacuate unnecessary personnel.

6.4. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.5. Methods and materials for containment and cleaning up

For containment	Absorb and or contain spill with inert material.
Methods for cleaning up	If recovery is not feasible, absorb with inert material. Place in a container suitable for disposal. Dispose of in accordance with current local legislation.

6.6. Reference to other sections

Refer to Section 8, Exposure controls and personal protection

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Handling temperature	Normal ambient temperature
Hygiene measures	Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating or drinking.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	Store in a dry, cool and well-ventilated place away from heat, sparks, open flames and any other ignition sources. Keep container closed when not in use.
Incompatible materials	Strong oxidizing agents
Maximum storage period	12 months, but may vary depending on storage conditions.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

8.1. Control parameters

Exposure limits:

Name	TWA - 8 hrs	STEL - 15 min
Methyl Ethyl Ketone	200ppm; 600 mg/m ³	300ppm; 885 mg/m ³
N-Butyl Acetate	150ppm; 710 mg/m ³	200ppm; 950 mg/m ³

8.2. Exposure controls

Engineering controls	Not required under normal conditions of use in a well-ventilated space.
Personal protective equipment	Use appropriate personal protection equipment (PPE).
Eye protection	Safety glasses
Skin and body protection	Use protective latex or nitrile gloves to prevent contact.
Respiratory protection	Not required under normal conditions of use in a well-ventilated space.
Other information	When using, do not eat or drink.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Aluminium coloured viscous liquid
Odour	Aromatic
Density (g/cm ³ @ 20°C)	Approximately 0.9
Flash point (°C)	Approximately 23
Solubility water	Insoluble
Solubility solvent	Soluble in most organic solvents

10. STABILITY AND REACTIVITY

Reactivity	None expected under normal conditions
Chemical stability	Stable under normal conditions
Possibility of hazardous reactions	None expected under normal conditions
Conditions to avoid	Open flames, sparks or other possible ignition sources.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Thermal decomposition may release carbon dioxide, carbon monoxide, smoke and fumes.

11. TOXICOLOGICAL INFORMATION

This product has not undergone any toxicological testing. Acute and chronic health effects are not expected as long as good hygiene and safety precautions are followed.

11.1. Acute toxicity: May cause respiratory irritation.

Components	Route of Exposure	Species/Test System	Result/Effect
Methyl Ethyl Ketone	Oral	Rat	LD ₅₀ : 3300 mg/kg
	Dermal	Rabbit	LD ₅₀ : 5000 mg/kg
n-Butyl Acetate	Oral	Rat	LD ₅₀ : 2800 mg/kg
	Dermal	Rabbit	LD ₅₀ : 1500 mg/kg

12. ECOLOGICAL INFORMATION

This product has not been tested for environmental effects. However, the ingredients indicate that it is dangerous to the environment.

Further ecological information

Components	Species/ test system	Result/Effect
Methyl Ethyl Ketone	Fish Toxicity	96hr LC ₅₀ (Leuciscus idus): 4600 – 4880 mg/l
	Daphnia Toxicity	48hr EC ₅₀ (Daphnia magna): >520 mg/l
N-Butyl Acetate	Fish Toxicity	96hr LC ₅₀ (Pimephales promelas): 18 mg/l
	Daphnia Toxicity	48hr LC ₅₀ (Daphnia magna): 44 mg/l
	Algae Toxicity	72hr EC ₅₀ (Green algae): 648 mg/l

General notes:

Water hazard class 1 (German regulation): slightly hazardous for water. Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13. DISPOSABLE CONSIDERATIONS

Sewage disposal recommendations	Do not dispose waste into sewer.
Waste disposal recommendations	Whatever cannot be saved for recovery or recycling should be disposed of in accordance with current local legislation.

14. TRANSPORT INFORMATION

14.1. UN Number

- **ADR, ADN, IMDG, IATA** UN 2059

14.2. UN Proper Shipping Name

- **ADR/AND, IMDG, IATA** Nitrocellulose solution, flammable

14.3. Transport hazard class

- **ADR, ADN, IMDG, IATA LABEL**



- **CLASS** 3 Flammable liquids

14.4. Packing group

- **ADR, ADN, IMDG, IATA** II

14.5. Environmental hazards

- **Marine pollutant (IMDG), Special marking (ADR/AND), Special marking (IATA)**
None

15. REGULATORY INFORMATION

15.1. Labelling Classified as a hazardous product

15.2. National legislation None

16. OTHER INFORMATION

16.1. Information sources

This SDS is prepared based on the information received from the suppliers

16.2. Full text of H-phrases referred to under Section 3

H225	Highly flammable liquid and vapour
H228	Flammable solid
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H360	May damage fertility or the unborn child
H411	Toxic to aquatic life with long lasting effects

16.3. Additional information

This document has been prepared in accordance with the SDS requirements of SANS 11014:2010

For intended use and applications see the Technical Data Sheet for the product. The information provided in this Safety Data Sheet is based on the present state of our knowledge. This data is intended to enable safety assessments to be made and should not be construed as guaranteeing specific properties. Recipients of our product must take responsibility for observing existing laws and regulations.

Revision date March 2020