



ALCOLIN STEEL EPOXY PUTTY

SAFETY DATA SHEET

1. IDENTIFICATION

1.1. Product identifier

Product name Alcolin Steel Epoxy Putty
Chemical family Epoxy Putty

1.2. Intended use of the product

Epoxy putty stick for sealing and repairing

1.3. Name, address, and telephone of the responsible party

Company: Permoséal (Pty) Ltd
Address: 1 Beverley Close, Montague Gardens, 7441, Cape Town, South Africa
Phone: +27-21-555-7400
Toll-free No. 0800-222-400
Website: www.alcolin.com

1.4. Emergency phone number

+27-21-555-7400

2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

GHS Classification This product is classified as a hazardous mixture

2.2. Label elements

GHS Labelling

- This product is classified and labelled according to the CLP regulation.
- Hazard pictograms



GHS07



GHS08



GHS05

2.3. Signal word Warning

2.4. Hazard determining components of labelling:

Reaction product: Bisphenol-A epichlorhydrin epoxy resin; silicon dioxide; diethylenetriamine

2.5. Hazard statements:

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

2.6. Precautionary statements:

P260	Do not breathe dust/fume/gas/mist/vapours/sprays.
P273	Avoid release to the environment.
P280	Wear protective gloves / eye protection.
P302+P352	If on skin: Wash with plenty of soap and water.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Seek medical attention.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/containers in accordance with national regulations

2.7. Additional information

Contains epoxy constituents. May produce an allergic reaction.

2.8. Other Hazards

No additional information available.

2.9. Unknown acute toxicity

No data available

3. COMPOSITION / INFORMATION ON INGREDIENTS

Mixture. This product is hazardous.

Ingredients	CAS Number	Contents (%)	Classification of Substance
Silicon dioxide	7631-86-9	40 - 50	Eye irrit.: Cat 2 Skin Irrit.: Cat 2 Acute tox.: Cat 4 STOT SE: Cat 3
Calcium carbonate	1317-65-3	20 - 40	Eye irrit.: Cat 2 Skin Irrit.: Cat 2 Eye dam.: Cat 1
Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)	25068-38-6	15 – 20	Eye irrit.: Cat 2 Skin Sens.: Cat 1 Skin Irrit.: Cat 2 Aquatic Chron.: Cat 2
Diethylenetriamine	9051-49-4	5 - 10	Skin Corr.: Cat 1B Skin sens.: Cat 1 Acute tox.: Cat 4
3-Mercapto-1,2-propanediol	96-27-5	1 - 10	Eye irrit.: Cat 2 Skin Irrit.: Cat 2 Acute tox.: Cat 4

4. FIRST-AID MEASURES

4.1. Description of first aid measures

General	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice.
Inhalation	Take victim into fresh air. In case of unconsciousness, place patient in a recovery position for transportation. Seek medical advice.
Skin contact	Wash skin with soap and water and rinse thoroughly. Seek medical attention if irritation persists.
Eye contact	Rinse cautiously with water for 15 minutes. Remove any contact lenses if present and easy to do. Continue rinsing. Obtain medical attention.
Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting. Obtain medical attention.

4.2. Most important symptoms and effects both acute and delayed

General	May cause irritation in the uncured state.
Inhalation	No known significant effects or critical hazards.
Skin contact	May cause an allergic skin reaction in the uncured state.
Eye contact	May cause serious eye irritation.
Ingestion	May be harmful or have adverse effects.

Indication of any immediate medical attention and special treatment needed

Note to physicians	Treat symptomatically
--------------------	-----------------------

5. FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media	Water, dry chemical powder, foam, carbon dioxide or sand
Unsuitable ext. media	Not applicable

5.2. Special hazards arising from the substance or mixture

Fire hazard	Not flammable
Explosion hazard	Product is not explosive

5.3. Advice for firefighters

Firefighting instructions	Exercise caution when fighting any chemical fire.
Protection during firefighting	Firefighters should wear full protective gear. Do not enter fire area without proper protective equipment, including respiratory protection.
Hazardous combustion products	Under certain conditions of combustion traces of toxic substances cannot be excluded.

6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

General measures	None.
------------------	-------

6.2. For non-emergency personnel

Protective equipment	Use appropriate personal protection equipment (PPE).
Emergency procedures	Evacuate unnecessary personnel.

6.3. For emergency personnel

Protective equipment	Use appropriate personal protection equipment (PPE).
Emergency procedures	Secure the area and evacuate unnecessary personnel.

6.4. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.5. Methods and materials for containment and cleaning up

For containment	Absorb and or contain spill with inert material.
Methods for cleaning up	If recovery is not feasible, absorb with inert material. Place in a container suitable for disposal. Dispose of in accordance with current local legislation.

6.6. Reference to other sections

Refer to Section 8, Exposure controls and personal protection

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Handling temperature	Normal ambient temperature
Hygiene measures	Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating or drinking.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	Store in a dry, cool and well-ventilated place. Keep container closed when not in use.
Incompatible materials	Strong oxidizing agents, organic peroxides, acids.
Maximum storage period	12 months, but may vary depending on storage conditions.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

8.1. Control parameters

There are no established exposure limits for this product.

8.2. Exposure controls

Engineering controls	Provide good ventilation when handling large quantities. No special measures are required if stored and handled as above.
Personal protective equipment	Use appropriate personal protection equipment (PPE).

Hand protection	Wear chemical resistant gloves.
Eye protection	Not required under normal conditions of use.
Skin and body protection	Not required under normal conditions of use.
Respiratory protection	Not required under normal conditions of use in a well-ventilated space.
Other information	When using, do not eat or drink.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Grey and brown soft solid
Odour	Mild odour when mixed
Density (g/cm ³)	Approx. 1.6
Solubility water	Insoluble

10. STABILITY AND REACTIVITY

Reactivity	None expected under normal conditions
Chemical stability	Stable under normal conditions
Possibility of hazardous reactions	None expected under normal conditions
Conditions to avoid	Direct sunlight. Extremely high or low temperatures. Exposure to moisture
Incompatible materials	Strong oxidizing agents, organic peroxides, acids
Hazardous decomposition products	Thermal decomposition may release carbon monoxide, carbon dioxide, nitrogen oxides, sulphur oxides

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

- Acute Toxicity:**

Ingredient	Result	Species	Dose
Bisphenol-A-(epichlorhydrin); epoxy resin	LD ₅₀ Dermal	Rabbit	23000 mg/kg
	LD ₅₀ Oral	Rat	>15000 mg/kg

12. ECOLOGICAL INFORMATION

This product has not been tested for environmental effects. It is however toxic to fish and other aquatic organisms and poses a danger to drinking water if even small quantities leak into the ground.

- Toxicity:**

Ingredient	Result	Species	Exposure
Bisphenol-A-(epichlorhydrin); epoxy resin	EC ₅₀ 11mg/l	Aquatic plants	72 hours
	EC ₅₀ 1.8mg/l	Daphnia	48 hours
	LC ₅₀ 2mg/l	Fish	96 hours
	Chronic NOEC 0.3mg/l	Daphnia	-

13. DISPOSABLE CONSIDERATIONS

Sewage disposal recommendations	Do not dispose waste into sewer.
Waste disposal recommendations	Whatever cannot be saved for recovery or recycling should be disposed of in accordance with current local legislation.

14. TRANSPORT INFORMATION

Road / rail transport	ADR / RID	Not regulated
Marine Transport	IMDG	Not regulated
Inland waterways	ADNR	Not regulated
Air transport	IATA	Not regulated

15. REGULATORY INFORMATION

- 15.1. Labelling** Classified as a hazardous product
- 15.2. National Legislation** None

16. OTHER INFORMATION

16.1. Information sources

This SDS is prepared based on the information received from the suppliers

16.2. Full text of H-phrases referred to under Section 3

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.

16.3. Additional information

This document has been prepared in accordance with the SDS requirements of SANS 11014:2010

For intended use and applications see the Technical Data Sheet for the product. The information provided in this Safety Data Sheet is based on the present state of our knowledge. This data is intended to enable safety assessments to be made and should not be construed as guaranteeing specific properties. Recipients of our product must take responsibility for observing existing laws and regulations.

Revision date July 2019